

UNCLASSIFIED

AD NUMBER

AD832104

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; MAY 1968. Other requests shall be referred to Air Force Office of Scientific Research, Attn: SREM, Washington, DC. This document contains export-controlled technical data.

AUTHORITY

AFOSR ltr, 1 Oct 1972

THIS PAGE IS UNCLASSIFIED

**ARCHIVE COPY  
DO NOT LOAN**



**LIFT-TO-DRAG RATIOS OF SEMISPAN  
DELTA WING CONFIGURATIONS AT  
SUPERSONIC AND HYPERSONIC MACH NUMBERS**

This document has been approved for public release  
its distribution is unlimited. *PER TAB 72-19  
Dtd 10 Oct, 72.*

**Larry J. Pfaff  
ARO, Inc.**

**May 1968**

This document is subject to special export controls  
and each transmittal to foreign governments or foreign  
nationals may be made only with prior approval of  
Air Force Office of Scientific Research (SREM),  
Washington, D. C.

This document may be further distributed by any  
holder only with specific prior approval of Air Force  
Office of Scientific Research (SREM), Washington, D. C.

**VON KÁRMÁN GAS DYNAMICS FACILITY  
ARNOLD ENGINEERING DEVELOPMENT CENTER  
AIR FORCE SYSTEMS COMMAND  
ARNOLD AIR FORCE STATION, TENNESSEE**

PROPERTY OF U. S. AIR FORCE  
AEDC LIBRARY  
AF 40(600)1200

AEDC TECHNICAL LIBRARY



# ***NOTICES***

When U. S. Government drawings specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

LIFT-TO-DRAG RATIOS OF SEMISPAN  
DELTA WING CONFIGURATIONS AT  
SUPERSONIC AND HYPERSONIC MACH NUMBERS

This document has been approved for public release

its distribution is unlimited. *PER TAB 72-19,  
Dtd 1 Oct, 72.*

Larry J. Pfaff  
ARO, Inc.

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Air Force Office of Scientific Research (SREM), Washington, D. C.

This document may be further distributed by any holder only with specific prior approval of Air Force Office of Scientific Research (SREM), Washington, D.C.

## FOREWORD

The work reported herein was done at the request of the Air Force Office of Scientific Research (AFOSR) for Aerospace Research Associates (ARA) under Program Element 6244501F, Project 9781, Task 978101.

The results of tests presented were obtained by ARO, Inc. (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), Air Force Systems Command (AFSC), Arnold Air Force Station, Tennessee, under Contract AF40(600)-1200. The tests were conducted from January 6 to 11, May 2 to 6, December 29, 1966 to January 3, 1967, and December 6 to 13, 1967 under ARO Project No. VT0640. This report contains data, not previously published, obtained during the early stages of the test program. The manuscript was submitted for publication on March 29, 1968.

Further dissemination of this report is restricted because of disclosure considerations relating to preliminary concepts by contractor personnel which were a part of this test.

Information in this report is embargoed under the Department of State International Traffic in Arms Regulations. This report may be released to foreign governments by departments or agencies of the U. S. Government subject to approval of the Air Force Office of Scientific Research (SREM), or higher authority within the Department of the Air Force. Private individuals or firms require a Department of State export license.

This technical report has been reviewed and is approved.

Donald H. Meyer  
Major, USAF  
AF Representative, VKF  
Directorate of Test

Roy R. Croy, Jr.  
Colonel, USAF  
Director of Test

**ABSTRACT**

Tests were conducted in the 40-in. supersonic and 50-in. hypersonic tunnels of the von Kármán Gas Dynamics Facility (VKF) to determine the maximum lift-to-drag ratios of a series of blunt leading edge, semispan delta wings having a 70-deg leading-edge sweep angle. Each wing configuration was comprised of triangular forward and tip panels and a rectangular main wing panel. Data were obtained at Mach numbers from 3 to 8 over an angle-of-attack range from -2 to 14 deg. Testing was primarily at a Reynolds number, based on the maximum wing root chord (48 in.), of  $14.4 \times 10^6$  with additional testing at Reynolds numbers of  $9.6 \times 10^6$  and  $3.4 \times 10^6$ . Selected results are presented showing the effect of forward panel bluntness and deflection, and Mach number on the wing lift-to-drag ratios.

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Air Force Office of Scientific Research (SREM), Washington, D. C.

This document has been approved for public release  
its distribution is unlimited. PER TAB 72-14,  
Dt'd 10 Oct, 72.

## CONTENTS

	<u>Page</u>
ABSTRACT . . . . .	iii
NOMENCLATURE . . . . .	vi
I. INTRODUCTION . . . . .	1
II. APPARATUS	
2.1 Wind Tunnels . . . . .	1
2.2 Models and Model Support. . . . .	2
2.3 Instrumentation and Techniques . . . . .	2
III. RESULTS AND DISCUSSION . . . . .	3
REFERENCES . . . . .	4

## APPENDIXES

## I. ILLUSTRATIONS

Figure

1. Model Details . . . . .	7
2. Sketch of Gap Variation Configurations . . . . .	8
3. General Arrangement of the Sidewall Angle-of-Attack Mechanism and Model Support Details	
a. Tunnel A. . . . .	9
b. Tunnel B. . . . .	9
4. Model Photographs	
a. Configuration 2 Installed in Tunnel A . . . . .	10
b. Forward Panel Sections . . . . .	11
5. Variation of $C_L$ and $C_D$ with Angle of Attack for Configuration 1. . . . .	12
6. Effect of Forward Panel Bluntness on L/D at $M_\infty = 4.02$ and $8.01$ . . . . .	13
7. Effect of Forward Panel Deflection on L/D at $M_\infty = 4.02$ and $8.01$ . . . . .	14
8. Variation of $(L/D)_{\max}$ with Mach Number . . . . .	15

## II. TABLE

I. Test Summary . . . . .	16
---------------------------	----

# **NOMENCLATURE**

$c$	Wing root chord (48 in. )
$C_D$	Forebody drag coefficient, $\text{drag}/q_\infty S$
$C_L$	Lift coefficient, $\text{lift}/q_\infty S$
$L/D$	Lift-to-drag ratio
$M_\infty$	Free-stream Mach number
$p_o$	Tunnel stilling chamber pressure, psia
$q_\infty$	Free-stream dynamic pressure, psia
$Re_c$	Free-stream Reynolds number based on wing root chord (48.00 in. )
$S$	Model reference area, see Fig. 1, $\text{in.}^2$
$T_o$	Tunnel stilling chamber temperature, $^\circ\text{R}$
$\alpha$	Model angle of attack, deg

## **MODEL NOMENCLATURE**

$F$	Forward wing panel
$T$	Tip wing panel
$W$	Main wing panel



## SECTION I INTRODUCTION

Aerospace Research Associates, Inc. (ARA, Inc.) is engaged in a program to determine the maximum lift-to-drag ratios of delta wing configurations. In support of this program, a series of static force tests were conducted on configurations of a 70-deg, blunt leading-edge, semispan delta wing. The model consisted of a main rectangular panel and triangular forward and tip panels. Various configurations were obtained by varying the bluntness of the forward panel, by deflecting the forward panel nose down, and by varying the chordwise and spanwise gaps between the panels. Other results of this test program are reported in Refs. 1 to 3.

Data were obtained at Mach numbers 3, 4, 4.5, 5, 6, and 8 at angles of attack from -2 to 14 deg. The primary Reynolds number, based on the wing root chord of 48 in., was  $14.40 \times 10^6$  with additional data being obtained at Reynolds numbers of  $9.60 \times 10^6$  and  $3.36 \times 10^6$ .

## SECTION II APPARATUS

### 2.1 WIND TUNNELS

Tunnel A is a continuous, closed-circuit, variable density wind tunnel with an automatically driven flexible plate nozzle and a 40- by 40-in. test section. The tunnel operates at Mach numbers 1.5 to 6 at maximum stagnation pressures from 29 to 200 psia, respectively, and stagnation temperatures up to 760°R ( $M_\infty = 6$ ). Minimum operating pressures range from about one-tenth to one-twentieth of the maximum pressures.

Tunnel B is a continuous, closed-circuit, variable density wind tunnel with axisymmetric contoured Mach 6 or 8 nozzles and a 50-in. - diam test section. The tunnel operates at stagnation pressures from 20 to 300 psia ( $M_\infty = 6$ ) and from 50 to 900 psia ( $M_\infty = 8$ ) and at stagnation temperatures up to about 1350°R. Additional information on both tunnels may be found in Ref. 4.

## 2.2 MODELS AND MODEL SUPPORT

The models, supplied by ARA (Fig. 1), were constant thickness (1.5 in.), semispan delta wings having hemispherical leading edges, 70-deg sweep angle, and a maximum root chord of 48 in. Wing configurations consisted of a triangular tip and rectangular main wing panel, and three different forward panels (Fig. 1). Additional configurations were obtained by deflecting the forward panel down 3 deg and by varying the gaps between the panels, as shown in Fig. 2.

Sectional views showing the sidewall mounted angle-of-attack mechanism and support for the three wing panels for Tunnels A and B are presented in Figs. 3a and b, respectively. A description of the angle-of-attack mechanism and support equipment is given in Ref. 1. An installation photograph of configuration 2 installed in Tunnel A is presented in Fig. 4a, and Fig. 4b is a photograph of the different nose shapes for the forward panel.

## 2.3 INSTRUMENTATION AND TECHNIQUES

Total wing forces and moments were measured with a six-component, force-type, strain-gage balance supplied and calibrated by the VKF. In addition, for selected runs, the forces and moments acting on the forward and tip wing panels were measured with five-component, moment-type, strain-gage balances also supplied and calibrated by the VKF. A different total wing balance was used for each tunnel.

Preceding the test, a range of static loadings was applied to the balances which simulated the range of model loadings obtained during the test. Listed below is the range of uncertainties, for the total wing balances, which correspond to the difference between the applied loads and the values calculated by the final data reduction balance equations. Since the balance was mounted perpendicular to the flow, the balance components listed correspond to the model component measured and are not necessarily the balance components normally used to obtain these forces and moments.

### TUNNEL A BALANCE

<u>Balance Component</u>	<u>Design Load</u>	<u>Maximum Static Loads</u>	<u>Maximum Model Loads</u>	<u>Uncertainties</u>
Normal Force, lb	600	250	325	±3.00
Axial Force, lb	600	50	35	±3.00

## TUNNEL B BALANCE

Balance Component	Design Load	Maximum Static Loads	Maximum Model Loads	Uncertainties
Normal Force, lb	1500	300	250	±5.00
Axial Force, lb	750	50	34	±3.00

Model base pressures were measured with the standard pressure system of each tunnel. The Tunnel A system utilizes 15-psid transducers referenced to a near vacuum. These transducers are calibrated for ranges of 15, 5, and 1 psia, and the precision of the system is estimated to be within 0.25 percent of full scale of the range being used. The Tunnel B system incorporates differential pressure transducers of 15-psid capacity referenced to a vacuum, and the uncertainty of measurement is considered to be not more than ±0.003 psia or ±0.5 percent, whichever is greater.

For both tunnels, the angle of attack is considered to be correct to within ±0.1 deg, and the centerline flow uniformity is within ±0.5 percent in Mach number.

A summary of the test program is presented in Table I; listed below are the test conditions at each Mach number for the primary Reynolds number,  $Re_c = 14.40 \times 10^6$ .

$M_\infty$	$p_o$ , psia	$T_o$ , °R	$q_\infty$ , psia
2.99	24.4	562	4.22
4.02	42.8	570	3.10
4.53	56.5	580	2.70
5.03	79.0	619	2.56
6.05	202.0	858	3.13
8.01	836.0	1351	3.81

### SECTION III

#### RESULTS AND DISCUSSION

Selected results of the tests at  $M_\infty = 4.02$  and 8.01 are presented in Figs. 5 through 8. In regard to these results, it should be noted that in many cases the data points shown are the result of fairings made through the test points to eliminate data scatter. This data scatter (primarily in drag) was the result of the method used to support the model wherein the

balance had to be located a long distance away from the wing center-of-pressure and center-of-gravity positions and, consequently, a large capacity balance, relative to the model air loads, had to be used.

The data of Fig. 5 for configuration 1 at  $M_\infty = 4.02$  and  $8.01$  typify the trends of  $C_L$  and  $C_D$  with angle of attack for all configurations and Mach numbers. The variation of the lift-to-drag ratio for various wing configurations at  $M_\infty = 4.02$  and  $8.01$  is shown in Figs. 6 and 7. Figure 6 shows the decrease obtained in  $L/D$  with increasing bluntness of the forward panel; and comparing Figs. 6 and 7, it can be seen that deflecting the forward panel  $-3$  deg also generally decreased  $L/D$  but that the same (or nearly so) maximum  $L/D$  value was obtained although at a higher angle of attack. For the basic configuration (1) at  $M_\infty = 4.02$ , there was little or no effect of the forward panel deflection at  $\alpha \geq 6$  deg.


No results are presented for the various gap configurations tested since the effect of the gaps on  $L/D$  were within the measurement precision.

Figure 8 presents the variation of  $(L/D)_{\max}$  with Mach number for various wing configurations. In general,  $(L/D)_{\max}$  decreased with increasing Mach number and with forward panel bluntness.


#### REFERENCES

1. Coats, Jack D. and Morgan, L. A. "Force Tests on Flat, Chambered, and Twisted Wings at Mach Numbers 3, 4, and 6." AEDC-TN-61-147 (AD326853), November 1961.
2. Pfaff, Larry J. "Force and Pressure Tests on a Semispan Delta Wing at Supersonic Speeds." AEDC-TR-65-165 (AD467448), August 1965.
3. Merz, Glenn H. "Force Tests of a Slotted Semispan Delta Wing Model at Hypersonic Mach Numbers." AEDC-TR-68-47, February 1968.
4. Test Facilities Handbook (Sixth Edition). "von Karman Gas Dynamics Facility, Vol. 4." Arnold Engineering Development Center, November 1966.

**APPENDIXES**  
**I. ILLUSTRATIONS**  
**II. TABLE**



Configuration	S, in. <sup>2</sup>
1,2	419.293
3,4	418.864
5,6	411.236



All Dimensions in Inches

Fig. 1 Model Details




Fig. 2 Sketch of Gap Variation Configurations






Fig. 3 General Arrangement of the Sidewall Angle-of-Attack Mechanism and Model Support Details







a. Configuration 2 Installed in Tunnel A  
Fig. 4 Model Photographs



b. Forward Panel Sections  
Fig. 4 Concluded

Fig. 5 Variation of  $C_L$  and  $C_D$  with Angle of Attack for Configuration 1






Fig. 6 Effect of Forward Panel Bluntness on L/D at  $M_\infty = 4.02$  and  $8.01$

Fig. 7 Effect of Forward Panel Deflection on  $L/D$  at  $M_\infty = 4.02$  and  $8.01$

Fig. 8 Variation of  $(L/D)_{max}$  with Mach Number

**TABLE I**  
**TEST SUMMARY**

$M_\infty$	$Re_c \times 10^{-6}$	Configuration					
		1	2	3	4	5	6
2.99	14.40	$\alpha_1$ and $A_1$	$\alpha_1$ and $A_1$	$\alpha_1$ and $A_1$	$\alpha_1$ and $A_1$	$\alpha_1$ and $A_1$	$\alpha_1$ and $A_1$
2.98	3.36	$\alpha_2$ and $A_1$		$\alpha_2$ and $A_1$		$\alpha_2$ and $A_2$	
4.02	14.40	$\alpha_2, A_1$ and $A_2^{***}$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$
4.53	14.40	$\alpha_2, A_1$ and $A_2^{***}$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$
4.50	3.36	$\alpha_2$ and $A_1$		$\alpha_2$ and $A_1$		$\alpha_2$ and $A_1$	
5.03	14.40	$\alpha_2, A_1, A_2,^{***}$ and $A_3$	$\alpha_2$ and $A_1$	$\alpha_2, A_1$ and $A_3$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$
5.02	9.60	$\alpha_2$ and $A_3$		$\alpha_2$ and $A_3$			
4.95	3.36	$\alpha_2, A_1$ and $A_3$		$\alpha_2, A_1$ and $A_3$		$\alpha_2$ and $A_1$	
5.95*	14.40	$\alpha_2, A_1$ and $A_3$	$\alpha_2$ and $A_1$	$\alpha_2, A_1$ and $A_3$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$
5.93*	9.60	$\alpha_2$ and $A_3$		$\alpha_2$ and $A_3$			
5.82*	3.36	$\alpha_2, A_1$ and $A_3$		$\alpha_2, A_1$ and $A_3$		$\alpha_2$ and $A_1$	
6.05**	14.40	$\alpha_2$ and $A_1$		$\alpha_2$ and $A_1$		$\alpha_2$ and $A_1$	
8.01	14.40	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$
7.91	3.36	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$	$\alpha_2$ and $A_1$

$M_\infty$	$Re_c \times 10^{-6}$	Gap Configuration				
		2	3	4	5	6
4.02	14.40	$\alpha_2$ and $A_2$	$\alpha_2$ and $A_2$	$\alpha_2$ and $A_2$	$\alpha_2$ and $A_2$	$\alpha_2$ and $A_2$
4.53		↓	↓	↓	↓	↓
5.03		↓	↓	↓	↓	↓
8.01		↓	↓	↓	↓	↓

Gap between panels = 0.020 in. except as noted

$\alpha_1$  = -2 to 9 deg

$\alpha_2$  = -2 to 14 deg

$A_1$  - Measured forces and moments on total wing and forward and tip panels

$A_2$  - Measured forces and moments on total wing only

$A_3$  - Configuration consisted of forward panel only

\*Tunnel A

\*\*Tunnel B

\*\*\*Configuration tested with gaps between panels equal to 0.015, 0.020, and 0.030 in.

## DOCUMENT CONTROL DATA - R &amp; D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

## 1. ORIGINATING ACTIVITY (Corporate author)

Arnold Engineering Development Center  
ARO, Inc., Operating Contractor  
Arnold Air Force Station, Tennessee

## 2a. REPORT SECURITY CLASSIFICATION

UNCLASSIFIED

## 2b. GROUP

N/A

## 3. REPORT TITLE

LIFT-TO-DRAG RATIOS OF SEMISPAN DELTA WING CONFIGURATIONS AT SUPERSONIC  
AND HYPERSONIC MACH NUMBERS

## 4. DESCRIPTIVE NOTES (Type of report and inclusive dates)

Jan. 6-11, May 2-6, Dec. 29, 1966 - Jan. 3, 1967; Dec. 6-13, 1967-Final

## 5. AUTHOR(S) (First name, middle initial, last name)

Larry J. Pfaff, ARO, Inc.

## 6. REPORT DATE

May 1968

## 7a. TOTAL NO. OF PAGES

22

## 7b. NO. OF REFS

4

## 8a. CONTRACT OR GRANT NO.

AF 40(600)-1200

## b. PROJECT NO.

9781

## c. Program Element 6244501F

## d. Task 978101

## 9a. ORIGINATOR'S REPORT NUMBER(S)

AEDC-TR-68-95

## 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)

N/A

10. DISTRIBUTION STATEMENT Subject to special export controls; transmittal to foreign governments or foreign nationals requires approval of AF Office of Scientific Research (SREM). Further distribution by holder requires approval of Air Force Office of Scientific Research (SREM), Washington, D.C.

## 11. SUPPLEMENTARY NOTES

Available in DDC

## 12. SPONSORING MILITARY ACTIVITY

Air Force Office of Scientific  
Research (SREM),  
Washington, D.C.

## 13. ABSTRACT

Tests were conducted in the 40-in. supersonic and 50-in. hypersonic tunnels of the von Kármán Gas Dynamics Facility (VKF) to determine the maximum lift-to-drag ratios of a series of blunt leading edge, semispan delta wings having a 70-deg leading-edge sweep angle. Each wing configuration was comprised of triangular forward and tip panels and a rectangular main wing panel. Data were obtained at Mach numbers from 3 to 8 over an angle-of-attack range from -2 to 14 deg. Testing was primarily at a Reynolds number, based on the maximum wing root chord (48 in.), of  $14.4 \times 10^6$  with additional testing at Reynolds numbers of  $9.6 \times 10^6$  and  $3.4 \times 10^6$ . Selected results are presented showing the effect of forward panel bluntness and deflection, and Mach number on the wing lift-to-drag ratios.

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Air Force Office of Scientific Research (SREM), Washington, D.C.

This document has been approved for public release  
its distribution is unlimited. PERTAB 72-19,  
Dt'd 1 Oct. 72.



14	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	supersonic flow hypersonic flow lift drag Delta Wing Configurations  <div>1-2 1. Triangular wings - - Lift 2     "                 "   - - Drag</div>						